



PC SELECT INFIELD CONDITIONER

Product Specifications

Product Data

Product:

Pro's Choice Select Sports Field Conditioner

Manufacturer:

Oil-Dri Corporation of America
914 Curie Drive, Alpharetta, GA 30005
1-800-648-1166

Processing/Shipping Location:

Ripley, MS 38663

Description:

Natural mineral with a blend of Montmorillinite, illite, and amorphous silica. 40% minimum & 60% minimum amorphous silica. Material must be processed via rotary kiln operation at temperatures above 1200° Fahrenheit. Material must be screened and de-dusted.

Installation:

The following formula will be a guide for installing PC Select into your infield or root zone area. Infields should be conditioned at approximately 15% to 20% by volume. We recommend PC Select be rototilled 1-4 inches deep. Root zones should be approximately 20% by volume 4-6 inches deep depending on soils used.

Mineral Classification:

Fuller's Earth, Montmorillinite
(Calcium-Bentonite)

Color/Appearance:

Reddish Orange

Technical Data

Product Specifications:	Typical Analysis	Test Procedure
Foreign material	None	SE307.01.01
Bulk density, lbs/ft ³	33.4 lb/ft ³	DN001.01.01
pH	5.3	IN001.01.01
Free moisture %	0.4%	VL003.03.02
Hardness %	91.6%	HD001.02.01
Wet Slaking %	3.8%	HD005.01.01
Dust index	1.17	PS005.02.02
Grind Distribution	-10 / +16	PS001.02.01
Sieve analysis %		
+6 mesh	0%	
-6/+8 mesh	2%	
-8/+16 mesh	92%	
-16 mesh	6%	

Item Numbers:

A45202G40: 50 lb bags, 40 bags / pallet
A42202: Bulk Bag
A41202: Bulk Truck

