



PC TURF SOIL CONDITIONER

Product Specifications

Product Data

Product:

Pro's Choice Turf Soil Conditioner

Manufacturer:

Oil-Dri Corporation of America
914 Curie Drive, Alpharetta, GA 30005
1-800-648-1166

Processing/Shipping Location:

Ripley, MS 38663

Description:

Natural mineral with a blend of Montmorillinite, illite, and amorphous silica. 40% minimum & 60% minimum amorphous silica. Material must be processed via rotary kiln operation at temperatures above 1200° Fahrenheit. Material must be screened and de-dusted.

Installation:

The following formula will be a guide for installing PC Turf into your root zone area. We recommend PC Turf to be rototilled 3-6 inches deep into the root zones at approximately 2000-4000 lbs. per 1000 sq. ft. for new construction and 250-500 lbs. per 1000 sq. ft. for aerification.

Mineral Classification:

Fuller's Earth, Montmorillinite
(Calcium-Bentonite)

Color/Appearance:

Tan/Grey

Technical Data

Product Specifications:	Typical Analysis	Test Procedure
Foreign material	None	SE307.01.01
Bulk density, lbs/ft ³	35 lb/ft ³	DN001.01.01
pH	5	IN001.01.01
Free moisture %	0.7%	VL003.03.02
Hardness %	89%	HD001.02.01
Wet Slaking %	1%	HD005.01.01
Dust index	2.7	PS005.02.02
Grind Distribution	-6 / +40	PS001.02.01
Sieve analysis %		
+6 mesh	11%	
-6/+12 mesh	62.6%	
-12/+20 mesh	25.3%	
-20 mesh	1.2%	

Item Number:

A45301G40: 50 lb bags, 40 bags / pallet

